

The slide protection barrier offers **added protection to your access road** by forming a barrier to prevent small and large vehicles from veering off the roadway. It's **quick and easy to install** and connects to the existing connecting points on the panels. Due to the design it still allows 3000mm width of clearance on the panels.

Comprised of separate components: base plate, pipe and end caps the slide protection barrier can be connected together to create different lengths and configurations. Light components that can be handled by one person and no plant is required for install. Structurally designed tube and base plate sections for maximum strength and durability. The barrier can withstand vehicles of up to 40tonnes by preventing them from veering off the roadway in unforeseeable circumstances.

KEY BENEFITS



QUICK AND EASY ASSEMBLY



CONNECTS TO EXISTING ROADWAY



HIGH VISIBILITY



NO GROUND PENETRATION



ADDED GROUND PROTECTION



SLIDE PROTECTION BARRIER

PRODUCT SPECIFICATION

Item	Dimensions	Approx Weight (kg)
Tube	114.3mm O/D 3.5mm wall thickness 2250mm long	22
Base Connector	10mm plate 400mm long	8
End Cap	450mm long	5



- >> The system comprises of Base Plates, Tubes and End Caps which are secured to the existing connecting points on the panels.
- >> The bright yellow finish provides high visibility along the designated length of the roadway; assisting driver awareness and highlighting the sensitivity of the site operation.





© 2023 TPA Portable Roadways Limited, all rights reserved. Specifications are subject to change without notice. Trademarks are the property of TPA Portable Roadways Limited or their respective owners. Product Design Protected by Patent(s). Document Issue date: 23/10/23 Document Version: 1.1

